## [2017-Aug.-UpdatedInstant Download Braindump2go 300-175 Exam Dumps 255Q[11-20

[Full Version!]2017 August New Updated 300-175 Exam Dumps with PDF and VCE Free Share! Following are some new 300-175 questions: 1.]2017 New 300-175 Exam Dumps (PDF & VCE) 255Q&As Download:https://www.braindump2go.com/300-175.html 2.]2017 New 300-175 Exam Questions & Answers Download:

https://drive.google.com/drive/folders/0B75b5xYLjSSNZjVxdkhhREFxblU?usp=sharing QUESTION 11Which option describes the possible result of a customer configuring a server pool that contains Cisco UCS B200 M2 and B250 M2 blades? A. A service profile cannot migrate automatically from one blade to another blade within the server pool due to hardware failure.B. You must decommission a blade server for the associated service profile to migrate to another blade in the server pool successfully.C. You must uncheck the Restrict Migration box in the service profile to allow service profile migration between blades in the server pool. D. After service profile migration, the server fails in boot from SAN due to differences in PCI device IDs. Answer: D OUESTION 12Which two options occur when a server discovery policy is invoked? (Choose two.) A. executes the qualification in the server discovery policy against the serverB. applies the scrub policy to the serverC. analyzes the inventory of the serverD. assigns the server to the selected organization, if configuredE. creates a service profile for the server with the identity burned into the server at time of manufacture Answer: AC QUESTION 13If a customer wants to maximize the capability of server mobility with the Cisco UCS deployment, what two options are Cisco recommended? (Choose two.) A. Configure a server inheritance policy.B. Configure a Virtual Media boot.C. Configure a hardware-based service profile with burned-in addresses and identities.D. Configure boot from SAN.E. Configure service profiles with resource pools. Answer: DE QUESTION 14You have a Cisco UCS B200 M2 server configured with 12 4-GB DDR3 1333-MHz dual-voltage memory DIMMs. You learned that the server memory speed is running at 1066 MHz instead. How can you configure the server to run at maximum memory speed? A. You cannot configure memory speed of 1333 MHz. The maximum memory speed of a Cisco UCS B200 M2 server with 12 4-GB DIMM is 1066 MHz.B. Memory speed of the ESX host is configurable on VMware vCenter.C. Create a BIOS policy. In the RAS Memory BIOS settings, select Performance Mode for LV DDR Mode.D. On the CIMC of the Cisco UCS B200 M2, select 1333 MHz in the Memory Speed option. Answer: C QUESTION 15Your systems engineer has determined all of the firmware versions that the server operating system supports. What steps are taken on Cisco UCS to avoid manual firmware upgrades on the blade servers? A. Use Cisco UCS Manager firmware management to upgrade all Cisco UCS blade servers to the same target firmware versions.B. Configure host firmware package and management firmware package policies and associate the firmware policies with the service profiles.C. Create a BIOS policy and define the host firmware package and management firmware package.D. Configure host firmware package and management firmware package policies and associate the firmware policies with the server pools. Answer: B QUESTION 16When you create a vHBA, what will you achieve by enabling persistent binding? A. This feature allows the binding of the SCSI targets to the vHBA, even across reboots.B. This feature allows the binding of the same WWPN from the pool to the vHBA, even across reboots.C. This feature allows the binding of the same WWNN from the pool to the vHBA, even across reboots.D. This feature allows the binding of the Fibre Channel uplink to the vHBA, even across reboots. Answer: A QUESTION 17Which two tasks enable jumbo frames on a Cisco UCS system? (Choose two.) A. In the LAN cloud on Cisco UCS Manager, configure MTU 9000 in the uplink interfaces.B. In the LAN cloud on Cisco UCS Manager, enable jumbo frames in Fabric A and Fabric B.C. In the LAN cloud on Cisco UCS Manager, configure MTU 9000 in the VLAN.D. In the LAN cloud on Cisco UCS Manager, define a QoS system class with MTU 9000.E. In the service profile, configure MTU 9000 in the vNIC.F. In the service profile, configure MTU 9000 in the virtual machine.G. In the service profile, configure MTU 9000 in the uplink interfaces. Answer: DE QUESTION 18Which three items represent some of the components to implement Cisco VM-FEX for Cisco Unified Computing System Manager B-Series blades? (Choose three.) A. Cisco VSM VMB. VEM installed on the VMware vCenter VEM in the VMware ESX or ESXi hostD. Cisco Unified Computing System Manager version 1.2 or higherE. serverC. VMware vCenter serverF. Fibre Channel VMFS volume Answer: CDE QUESTION 19Which three items represent some of the features that can be defined in a Cisco Unified Computing System Manager port profile? (Choose three.) A. QoS policyB. ACL C. NetFlowD. port securityE. network control policyF. VLAN or VLANs Answer: AEF QUESTION 20Which three items must be configured in the Port Profile Client in Cisco Unified Computing System Manager? (Choose three.) A. port profileB. DVSC. data centerD. folderE. VMware vCenter IP addressF. VM port group Answer: BCD !!!RECOMMEND!!! 1.]2017 New 300-175 Exam Dumps (PDF & VCE) 255Q&As Download:https://www.braindump2go.com/300-175.html 2.|2017 New 300-175 Study Guide Video: YouTube Video: YouTube.com/watch?v=zm6ho1Bw02E