## [September-2020Instant Download Braindump2go 300-425 Dumps 300-425 800[027-045

September/2020 Latest Braindump2go 300-425 Exam Dumps with PDF and VCE Free Updated Today! Following are some new 300-425 Real Exam Questions!QUESTION 27An engineer has performed a predictive site survey for high-speed data and voice in an indoor office. What is the recommended data rate with -67 dBm signal level for optimal VoWLAN design?A. 6 Mbps on 802.11 bgnB. 24 Mbps on 802.11 bgnC. 12 Mbps on 802.11 anD. 24 Mbps on 802.11 anAnswer: BQUESTION 28An engineer has configured guest anchoring for a newly created SSD however, the mobility tunnels are not up, and EPING is failing from the foreign WLC to the anchor WLC. Which traffic flow must be allowed at the firewall to enable the communication? A. UDP port 16666B. IP protocol 97C. UDP port 97D. TCP port 97Answer: AQUESTION 29Which statement about creating a mobility group is true, excluding mobility anchors?A. Each WLC must use the same mobility name and be defined as a peer in each other's static mobility members list.B. If WLCs with HA SSO are deployed, each WLC in the WLC HA pair considered separately as a mobility peer.C. The WLCs do not have to be of the same model or type to be a member of a mobility group, however each member should be running different software versions.D. A mobility groups does not require all WLCs in the group to use the same virtual IP address. Answer: BQUESTION 30A wireless network consultant must assess an existing wireless LAN controller. Which section must the consultant check before replacing the old APs with APs that are IEEE 802.11ac-capable?A. number of AP licensesB. controller PSUC. throughput capacityD. software versionAnswer: AQUESTION 31A customer is concerned about mesh backhaul link security. Which level of ecnryption does the backhaul link use?A. hashB. AESC. WEPD. 3DESAnswer: BQUESTION 32Clustering Cisco WLCs into a single RF group enables the RRM algorithms to scale beyond the capabilities of a single Cisco WLC. How many WLC and APs in an RF group can the controller software scale up to in WLC release 8.9 depending on the platform? A. up to 20 WLCs and 1000 APsB. up to 20 WLCs and 3000 APsC. up to 20 WLCs and 4000 APsD. up to 20 WLCs and 6000 APsAnswer: DQUESTION 33During a client roaming event, which device is responsible for communicating the new Layer 2 EID mapping of a wireless supplicant to the fabric domain?A. WLCB. BNC. CP2D. CP1Answer: AQUESTION 34Multiple WLCs are implemented in a high-availability configuration in a mobility group. APs are deployed with only a primary controller assigned. By default, which mobility group member controller do the orphaned APs join in the event of a failed controller? A. controller with the most available AP free license capacity B. controller with the lowest percent of associated APs per license capacity C. controller with the least CPU utilization over the last reporting period D. controller with the least number of associated APsAnswer: DQUESTION 35Which two criteria must be considered when conducting an outdoor bridge site survey? (Choose two.)A. near-far effectB. weatherC. traffic lightsD. power linesE. Fresnel zoneAnswer: ADQUESTION 36A customer has two Cisco 550B WLCs that manage all the access points in their network and provide N+1 redundancy and load balancing. The primary Cisco WLC has 60 licenses and the secondary Cisco WLC has 40. The customer wants to convert the N+1 model to an HA model and provide SSO. Configuration must be performed during a maintenance window. After performing all the configurations on both controllers, the config redundancy unit secondary command is issued on the secondary Cisco WLC and it fails. Which parameter needs to be in place to complete the configuration? A. A cable in the RP portB. The secondary Cisco WLC needs a minimum of 50 base licensesC. The primary Cisco WLC is already set as the secondary unit.D. SSO needs to be enabledAnswer: BQUESTION 37A wireless engineer is hired to design a network for six buildings with a WLC in each building to support the access points. Which type of wireless architecture is being used? A. distributed deployment B. autonomous deploymentC. unified deploymentD. centralized deploymentAnswer: AQUESTION 38A wireless engineer is hired to troubleshoot wireless network issues and discovers that the customer is using 802 11 ac access points with 80 MHz-wide channels in a high-density environment. Which solution addresses these issues? A. Disable RRM on the WLC.B. Disable TPC on the WLCC. Decrease the channel width.D. Increase the minimum data rate supportedAnswer: CQUESTION 39You are designing a WLAN for 50 branch offices that require central management. Which controller architecture do you use? A. per-branch local controllers B. anchor controllersC. FlexConnect controllersD. autonomous access pointsAnswer: CQUESTION 40A customer has determined that a cable run for a low-throughput RF design is not economically feasible to install. Which two access point modes can alleviate these customer concerns? (Choose two.)A. bridgeB. snifferC. Flex+BridgeD. FlexConnectE. localAnswer: ADQUESTION 41Which two considerations must a network engineer have when planning for voice over wireless roaming? (Choose two.)A. reauthentication introduces gaps in a voice conversation.B. Roaming time increases when using 802.1x + Cisco Centralized Key Manegement.C. Roaming occurs when the phone has seen at least four APs.D. Roaming occurs when the phone has reached -80 dBs or below.E. Roaming with only 802.1x authentication requires full reauthentication. Answer: AEQUESTION 42An engineer must create data link redundancy for the company's Cisco Wireless LAN controller. The engineer has decided to configure

LAG-based redundancy instead of port-based redundancy. Which three features of LAG-based redundancy influenced this decision? (Choose three.)A. Packets are always sent out on the same port they are received on.B. All interface traffic passes as long as one port is up.C. The same port has multiple untagged dynamic interfaces.D. Interface connection to two separate nonstacked switches is available.E. Full bandwidth of all links is available.F. Ports are grouped into multiple LAGs.Answer: ABFQUESTION 43An engineer must speed up the reauthentication delays that are being experienced on the wireless infrastructure by deploying a key-caching mechanism. Which mechanism must be configured? A. PEAPB. FTC. PMFD. GTK-randomizationAnswer: BQUESTION 44A customer is running a guest WLAN with a foreign/export-anchor setup. There is one anchor WLC in the US and two in Europe. Anchor WLC priorities are used to prefer local anchors. During a routine network audit, it is discovered that a large number of guest client sessions in the US are anchored to the WLCs in Europe. Which reason explains this behavior?A. The foreign WLC failed and recovered.B. The US anchor WLC failed and recovered.C. The US anchor WLC is anchored to itself with a priority value of zero.D. The anchor WLC is in the same mobility group. Answer: BOUESTION 45Which non-Wi-Fi interferer can be identified by Metageek Chanalyzer?A. PDAsB. jammersC. smartphones D. printersAnswer: BResources From:1.2020 Latest Braindump2go 300-425 Exam Dumps (PDF & VCE) Free Share: https://www.braindump2go.com/300-425.html2.2020 Latest Braindump2go 300-425 PDF and 300-425 VCE Dumps Free Share: https://drive.google.com/drive/folders/116pgsScHZoMX\_x10f-SEvzUZ9ec2kgWd?usp=sharing3.2020 Free Braindump2go 300-425 PDF Download:https://www.braindump2go.com/free-online-pdf/300-425-Dumps(52-63).pdf

https://www.braindump2go.com/free-online-pdf/300-425-PDF(40-51).pdf

https://www.braindump2go.com/free-online-pdf/300-425-PDF-Dumps(16-27).pdf

https://www.braindump2go.com/free-online-pdf/300-425-VCE(28-39).pdf

https://www.braindump2go.com/free-online-pdf/300-425-VCE-Dumps(64-74).pdfFree Resources from Braindump2go,We Devoted to Helping You 100% Pass All Exams!